

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 September 2005 (01.09.2005)

PCT

(10) International Publication Number
WO 2005/080836 A1

(51) International Patent Classification⁷: **F16J 15/16 //**
15/40, 1/09, 9/20

(21) International Application Number:
PCT/SE2005/000279

(22) International Filing Date: 25 February 2005 (25.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0400442-0 25 February 2004 (25.02.2004) SE

(71) Applicant and

(72) Inventor: ADOLFSSON, Bengt [SE/SE]; Lundagatan 50,
S-117 27 Stockholm (SE).

(74) Agent: EHRNER & DELMAR PATENTBYRÅ AB;
Box 10316, S-100 55 Stockholm (SE).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: SEALING ARRANGEMENT FOR RELATIVELY MOVABLE PARTS AND DEVICE INCLUDING SUCH A SEAL-
ING ARRANGEMENT



(57) Abstract: A sealing arrangement for two relatively movable first and second parts and including a sealing ring positioned in a groove on one of the parts for sealing contact against the other one of the parts, so as to separate a first side of the sealing ring from a second side of the sealing ring, wherein the sealing ring is positioned in a sealing ring seat formed as a groove in the circumference of one of the parts, including liquid supply means for supplying liquid under pressure to the second side of the sealing ring, and means for balancing the pressure of the supplied liquid in the region of the sealing ring, whereby forces on the sealing ring resulting from the pressure prevailing on the first side of the sealing ring are counteracted and balanced in such a way that in operation the sealing ring is essentially free-floating in the groove. The invention also concerns a reciprocating piston device including such a sealing arrangement.